

IN THE CLAIMS

Please amend the following of the claims which are pending in the present application:

1. (Original) An optical system (10, 40) for observing multiple objects (33, 34; 61, 63) situated distal from one another, having a camera unit (11, 42) comprising a first prism unit (13, 43), which is situated on the optical axis (12, 41) and/or in the beam path (15, 47) of the camera unit, for producing two partial beam paths (18, 19; 48, 49), as well as two object prism units (20, 21; 51, 52), each of which is situated in a partial beam path and assigned to an object.

2. (Original) The optical system according to Claim 1,
characterized in that
an illumination unit (29, 30; 57, 58) is assigned to each object prism unit (20, 21; 51, 52).

3. (Original) The optical system according to Claim 2,
characterized in that
the illumination units (29, 30; 57, 58) are implemented as light-emitting semiconductor components.

4. (Original) The optical system according to Claim 3,

characterized in that

the illumination units are implemented as light-emitting diodes.

5. (Currently amended) The optical system according to ~~one of the preceding~~
~~claims~~ claim 1,

characterized in that

the output beam paths (22, 23) of the object prism units (20, 21) run
transversely to and in the same direction as the optical axis (12) of the camera unit
(11).

6. (Original) The optical system according to Claim 5,

characterized in that

illumination beam paths (31, 32) implemented between the object prism units
(20, 21) and the illumination units (29, 30) run transversely to the optical axis (12)
of the camera unit (11).

7. (Original) The optical system according to Claim 5,

characterized in that

the prism unit (13) has two optical boundary faces (16, 17), which are situated
perpendicular to one another and are each angled at 45° to the optical axis (12) of
the camera unit (11).

8. (Currently amended) The optical system according to ~~one of Claims 5 to 7~~
claim 5,

characterized in that

the object prism units (20, 21) may have their distance changed.

9. (Currently amended) The optical system according to ~~one of Claims 5 to 8~~
claim 5,

characterized in that

the illumination units (29, 30) may have their distance changed together with
the object prism units (20, 21).

10. (Currently amended) The optical system according to ~~one of Claims 1~~
~~through 4~~ claim 1,

characterized in that

the output beam paths (48, 49) of the object prism units (51, 52) run
transversely and in the opposite direction to the optical axis (41) of the camera unit
(42).

11. (Currently amended) The optical system according to Claim ~~[[11]]~~ 10,

characterized in that

the illumination beam paths (59, 60) implemented between the object prism

units (51, 52) and the illumination units (57, 58) run parallel to the optical axis (41) of the camera unit (42).

12. (Original) The optical system according to Claim 11,
characterized in that

the prism unit (43) has a first optical boundary face (45), which on the optical axis (41) of the camera unit (42) reflects a first partial beam path (48) in the direction of the first object (61) and is transparent to a second beam path (49), and which is angled by 45° to the optical axis, a second optical boundary face (50) situated perpendicular to the optical axis being positioned downstream from said first optical boundary face for reflecting the second partial beam path toward the first optical boundary face and reflecting the second partial beam path in the direction of the second object (63).